

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Goof Off Gunk & Adhesive Remover

Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113

Phone Number: (901)775-0100

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Removes gum, adhesives, stickers, crayon, lipstick, wax, grease, etc. from most surfaces.

Product Code: FG791, FG792

Additional Information This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 3
Acute Toxicity: Inhalation, Category 4
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Skin Sensitization, Category 1
Specific Target Organ Toxicity (single exposure), Category 3



GHS Signal Word: **Warning**

GHS Hazard Phrases: H226: Flammable liquid and vapor.
H332: Harmful if inhaled.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.

GHS Precaution Phrases: P233: Keep container tightly closed.
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P243: Take precautionary measures against static discharge.
P242: Use only non-sparking tools.
P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P362+364: Take off contaminated clothing and wash it before reuse.
P272: Contaminated work clothing should not be allowed out of the workplace.

GHS Response Phrases: P370+378: In case of fire, use dry chemical powder to extinguish.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Goof Off Gunk & Adhesive Remover

Printed: 02/09/2016

Revision: 02/04/2016

Supersedes Revision: 04/15/2015

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER/doctor if you feel unwell.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P321: Specific treatment see instructions on label.

P332+313: If skin irritation occurs, get medical advice/attention.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists, get medical advice/attention.

P333+313: If skin irritation or rash occurs, seek medical advice/attention.

GHS Storage and Disposal Phrases:

P403+235: Store in cool/well-ventilated place.

P501: Dispose of contents/container according to local, state and federal regulations.

P403+233: Store container tightly closed in well-ventilated place - if product is as volatile as to generate hazardous atmosphere.


P405: Store locked up.

Emergency Overview:

Eye and skin irritant. May be harmful if swallowed.

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL		0
PPE		X



HMIS:

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.

EYES: Can cause moderate to severe eye irritation and damage to the cornea. May cause discomfort, pain, redness, excess blood flow, and corneal clouding and swelling.

SKIN: Can cause inflammation of the skin and dermatitis. Repeated exposure may cause skin cracking, flaking or drying, redness, pain, blistering, and a rash. May enter the body through open lesions, cuts, abrasions, etc., and produce systemic injury.

INHALATION: Can cause respiratory irritation. May cause nose and throate irritation. May cause coughing and a headache.

INGESTION: Potassium ingestion can cause a slow, weak pulse, irregularities in heart rhythm, heart block and eventual fail in blood pressure. May produce diarrhea, bloated stomach, and occasional vomiting. May cause severe gastrointestinal tract irritation with nausea, vomiting and possible burns. May be harmful if swallowed.

CHRONIC OVEREXPOSURE EFFECTS:

2-Butoxyethanol: In animals, effects have been reported on blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits. In long term animal studies, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans.

TARGET ORGANS: blood, kidney, liver, respiratory system, heart, stomach

PRIMARY ROUTES OF ENTRY: skin, ingestion, inhalation

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	<11.0 %
5989-27-5	d-Limonene	<10.0 %
143-18-0	Oleic acid potassium salt	< 6.0 %
100-51-6	Benzenemethanol {Benzyl alcohol}	< 6.0 %

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:
 Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:
 Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:
 Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:
 If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down.

5. FIRE FIGHTING MEASURES

NFPA Class II

Flash Pt: 137.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Use carbon dioxide, dry powder, water spray, or foam.

Unsuitable Extinguishing Media: Solid streams of water may be ineffective and spread material.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Product does not sustain combustion.

Flammable Properties and Hazards: This is a flammable liquid as per 49 CFR 173.120. This product does not sustain combustion as per the exemption in 49 CFR 173 Appendix H.

Flammability Classification:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling: Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing: Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	No data.
5989-27-5	d-Limonene	No data.	No data.	No data.
143-18-0	Oleic acid potassium salt	No data.	No data.	No data.
100-51-6	Benzenemethanol {Benzyl alcohol}	No data.	No data.	No data.

SAFETY DATA SHEET

Goof Off Gunk & Adhesive Remover

Page: 5

Printed: 02/09/2016

Revision: 02/04/2016

Supersedes Revision: 04/15/2015

Respiratory Equipment (Specify Type):

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection:

Safety glasses should be worn during normal handling of this material.

Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.

Protective Gloves:

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing:

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

Work/Hygienic/Maintenance Practices:

Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

SAFETY DATA SHEET
Goof Off Gunk & Adhesive Remover

Page: 6

Printed: 02/09/2016

Revision: 02/04/2016

Supersedes Revision: 04/15/2015

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid
Appearance and Odor: Clear orange gel.
Melting Point: No data.
Boiling Point: No data.
Autoignition Pt: No data.
Flash Pt: 137.00 F Method Used: Setaf flash Closed Cup (Rapid Setaf flash)
Explosive Limits: LEL: No data. UEL: No data.
Specific Gravity (Water = 1): 0.9693
Density: 8.12 LB/GL
Vapor Pressure (vs. Air or mm Hg): No data.
Vapor Density (vs. Air = 1): No data.
Evaporation Rate: No data.
Solubility in Water: soluble
pH: 7 - 8
Percent Volatile: No data.
VOC / Volume: 191.0000 G/L

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: No data available.
Incompatibility - Materials To Avoid: Oxidizers, strong acids
Hazardous Decomposition or Byproducts: Can include aldehydes, ketones, organic acids, oxides of citrus terpenes
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

Carcinogenicity/Other Information: CAS# 111-76-2:
 Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.
 Result:
 Behavioral: Ataxia.
 Nutritional and Gross Metabolic: Weight loss or decreased weight gain.
 - Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.
 Result:
 Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).
 Effects on Embryo or Fetus: Other effects to embryo.
 Specific Developmental Abnormalities: Musculoskeletal system.
 - Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.
 Result:
 Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
 Result:
 Effects on Newborn: Apgar score (human only).
 Effects on Newborn: Other neonatal measures or effects.
 Effects on Newborn: Drug dependency.
 - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

IARC 3: Not Classifiable as to Carcinogenicity in Humans.
 ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.
5989-27-5	d-Limonene	n.a.	3	n.a.	n.a.
143-18-0	Oleic acid potassium salt	n.a.	n.a.	n.a.	n.a.
100-51-6	Benzenemethanol {Benzyl alcohol}	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state, and federal laws.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: DOT exempt per 49 CFR 173 Appendix H.

DOT Hazard Class:

UN/NA Number:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230
5989-27-5	d-Limonene	No	No	No
143-18-0	Oleic acid potassium salt	No	No	No
100-51-6	Benzenemethanol {Benzyl alcohol}	No	No	No

This material meets the EPA Yes No **Acute (immediate) Health Hazard**
'Hazard Categories' defined Yes No **Chronic (delayed) Health Hazard**
for SARA Title III Sections Yes No **Fire Hazard**
311/312 as indicated: Yes No **Sudden Release of Pressure Hazard**
 Yes No **Reactive Hazard**

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
5989-27-5	d-Limonene	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
143-18-0	Oleic acid potassium salt	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
100-51-6	Benzenemethanol {Benzyl alcohol}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

Regulatory Information Statement: All components of this material are listed on the TSCA Inventory or are exempt.

16. OTHER INFORMATION

Revision Date: 02/04/2016
Preparer Name: EHS Department
Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other

SAFETY DATA SHEET
Goof Off Gunk & Adhesive Remover

Page: 9

Printed: 02/09/2016

Revision: 02/04/2016

Supersedes Revision: 04/15/2015

information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.